



# Product Evaluation

WIN2119 | 0916

Engineering Services Program

*The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).*

*This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.*

*This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.*

*For more information, contact TDI Engineering Services Program at (800) 248-6032.*

**Evaluation ID:** WIN-2119

**Effective Date:** September 1, 2016

**Re-evaluation Date:** September 2020

**Product Name:** Series 10320 Hermosa, Vinyl Fixed Window, Non-Impact Resistant

**Manufacturer:** Milgard Manufacturing, Inc.  
1010 54<sup>th</sup> Avenue East  
Tacoma, WA 98424  
(253) 896-7631

### General Description:

System	Description	Label Rating	Design Pressure Rating
1	Series 10320 Vinyl Fixed Window (FIN)	CW PG35 96 X 72-FW	+35 / -35 psf

### Product Dimensions:

System	Overall Size	Fixed Sash Daylight Opening
1	96" x 72"	91" x 67"

### Product Identification (Certification Label on Window):

System		
1	Certification Agency	AAMA
	Manufacturer's Name or Code Name	MG-14
	Product Name	Series 10320 PW Vinyl Fixed Window
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-08

**Impact Resistance:**

System	Impact Resistant	Requirement
1	No	Provide an impact protective system when installing the product in areas that require windborne debris protection.

**Acceptance of Smaller Assemblies:** Door assemblies with dimensions equal to or smaller than those specified are acceptable with the limitations specified in this report.

**Installation:**

System		
1	Type of Installation	Fin Mount
	Wall Framing	Southern Pine
	Fasteners	No. 8 screws
	Fastener Location/Spacing	The fasteners must be located at 4" or less from each corner and spaced 12" approximately thereafter around the perimeter through pre-punched fin of the frame.
	Fastener Penetration	Minimum 1-1/2" penetration into the wall framing

**Note:** Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC, the IBC, and the Texas Revisions.