

PO Box 12030 | Austin, TX 78711 | 800-578-4677 | tdi.texas.gov

Product Evaluation

WIN2339 | 0523

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: WIN-2339 **Effective Date:** May 1, 2023

Re-evaluation Date: November 2025

Product Name: Premium Vinyl (V-4500) Rotary Operated Awning Windows, Impact Resistant

Manufacturer: JELD-WEN Windows and Doors

Research and Development

3737 Lakeport Blvd. Klamath Falls, OR 97601

(541) 850-2650

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Premium Vinyl Rotary	LC-PG50 (48 x 36)-AP	+50 / -55 psf
	Operated Awning Window; X	Missile Level C	+50 / -55 psi
2	Premium Vinyl Rotary	LC-PG50 (48 x 36)-AP	LEO / EE nof
	Operated Awning Window; X	Missile Level D	+50 / -55 psf
3	Premium Vinyl Rotary Operated	LC-PG50 (144 x 36)-AP	LEO / EE pef
	Triple Awning Window; XXX	Missile Level C	+50 / -55 psf
4	Premium Vinyl Rotary Operated	LC-PG50 (144 x 36)-AP	LEO / EE pef
	Awning Window; XXX	Missile Level D	+50 / -55 psf

Product Dimensions:

System	Overall Size	Operable Sash Size
1	48" x 36"	46-1/2" x 34-1/2"
2	48" x 36"	48-7/16" x 34-1/2"
3	144" x 36"	Three: 46.18" x 34.65"
4	144" x 36"	Three: 46.18" x 34.49"

Product Identification (Certification Label on Window):

System			
	Certification Agency	AAMA	
	Manufacturer's Name or Code Name	JW-12, JW-14, JW-18	
1	Product Name	PREM VYL (V-4500) Rotary	
1		Operated AWN	
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11	
		AAMA 506; Missile Level C	
	Certification Agency	AAMA	
	Manufacturer's Name or Code Name	JW-12, JW-14, JW-18	
2	Product Name	PREMIUM VYL (V-4500) Rotary	
		Operated AWN	
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11	
		AAMA 506; Missile Level D	
	Certification Agency	AAMA	
	Manufacturer's Name or Code Name	JW-12, JW-14, JW-18	
3	Product Name	PREM VYL (V-4500) Rotary	
		Operated Triple AWN	
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11	
		AAMA 506; Missile Level C	
	Certification Agency	AAMA	
4	Manufacturer's Name or Code Name	JW-12, JW-14, JW-18	
	Product Name	PREM VYL (V-4500) Rotary	
		Operated Triple AWN	
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11	
		AAMA 506; Missile Level D	

Impact Resistance:

inpact Kesistance.		
System	Impact Resistant	Requirement
1, 3	Yes	These products satisfy TDI's criteria for protection from windborne debris. Install in areas where the basic ultimate windspeed is less than 150 mph and greater than one mile from the coastline. Install the assemblies at a height on the structure that does not exceed the design pressure rating for the assemblies.

Impact Resistance:

System	Impact Resistant	Requirement
2, 4	Yes	These products satisfy TDI's criteria for protection from windborne debris. Install the assemblies at a height on the structure that does not exceed the design pressure rating for the assemblies.

Installation:

System			
1	Type of Installation	Lastallia and a samith IELD WENT duration N	
	Wall Framing	Install in accordance with JELD-WEN drawing No.	
	Fasteners	D014779, titled "Premium Vinyl Awning Window Impact," dated May 4, 2021. Signed and sealed b Joseph A. Reed, P.E. on May 13, 2021.	
	Fastener Location/Spacing		
	Fastener Penetration	703cp11 A. Need, 1.E. 011 Way 13, 2021.	
	Type of Installation	Install in accordance with JELD-WEN drawing No. D014549, titled "Premium Vinyl Awning Window- Impact," dated May 5, 2021. Signed and sealed by Joseph A. Reed, P.E. on May 13, 2021.	
2	Wall Framing		
	Fasteners		
	Fastener Location/Spacing		
	Fastener Penetration	703epii A. Need, I .L. 011 Way 13, 2021.	
	Type of Installation	Install in accordance with IELD WENT drawing No	
	Wall Framing	Install in accordance with JELD-WEN drawing No.	
3	Fasteners	D014415, titled "Premium Vinyl Awning Window XXX-Impact," dated May 5, 2021. Signed and sealed by Joseph A. Reed, P.E. on May 13, 2021.	
	Fastener Location/Spacing		
	Fastener Penetration		
	Type of Installation	Located in a considerate with JELD MATERIAL duration of the	
4	Wall Framing	Install in accordance with JELD-WEN drawing North D014626, titled "Premium Vinyl Awning Window XXX-Impact," dated May 6, 2021. Signed and sealed by Joseph A. Reed, P.E. on May 13, 2021	
	Fasteners		
	Fastener Location/Spacing		
	Fastener Penetration		

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.