# **TDI** Texas Department of Insurance

PO Box 12030 | Austin, TX 78711 | 800-578-4677 | tdi.texas.gov

### **Product Evaluation**

 WIN2599 | 0321
 Engineering Services Program

 The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

 This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

 This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall

Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

**Evaluation ID:** WIN-2599

Effective Date:March 1, 2021Re-evaluation Date:March 2024

Product Name: Impervia Fiberglass Model 2 Vent Awning Windows, Non-Impact Resistant

Manufacturer: Pella Corporation 102 Main St. Pella, Iowa 50219 (641) 621-1000

#### **General Description:**

| System | Description  | Label Rating             | Design Pressure<br>Rating |
|--------|--|--------------------------|---------------------------|
| 1      | Impervia Fiberglass Model 2<br>Vent Awning Windows | LC-PG50 (41.5 x 41.5)-AP | +50 / -60 psf             |
| 2      | Impervia Fiberglass Model 2<br>Vent Awning Windows | LC-PG50 (41.5 x 59.5)-AP | +50 / -60 psf             |
| 3      | Impervia Fiberglass Model 2<br>Vent Awning Windows | LC-PG50 (53.5 x 21)-AP   | +50 / -50 psf             |
| 4      | Impervia Fiberglass Model 2<br>Vent Awning Windows | LC-PG50 (53.5 x 29.5)-AP | +50 / -50 psf             |
| 5      | Impervia Fiberglass Model 2<br>Vent Awning Windows | LC-PG50 (53.5 x 41.5)-AP | +50 / -50 psf             |
| 6      | Impervia Fiberglass Model 2<br>Vent Awning Windows | LC-PG50 (53.5 x 59.5)-AP | +50 / -50 psf             |

#### **General Description:**

| System | Description  | Label Rating             | Design Pressure<br>Rating |
|--------|--|--------------------------|---------------------------|
| 7      | Impervia Fiberglass Model 2<br>Vent Awning Windows | LC-PG30 (59.5 x 41.5)-AP | +30 / -30 psf             |
| 8      | Impervia Fiberglass Model 2<br>Vent Awning Windows | LC-PG30 (59.5 x 59.5)-AP | +30 / -30 psf             |

#### **Product Dimensions:**

| System | Overall Size       | Operable Sash Size    |
|--------|--------------------|-----------------------|
| 1      | 41-1/2" x 41-1/2"  | 38-15/16" x 38-15/16" |
| 2      | 41-1/2" x 59-1/2"  | 38-15/16" x 56-15/16" |
| 3      | 53-1/2" x 21"      | 50-15/16" x 18-7/16"  |
| 4      | 53-1/2" x 29-1/2"  | 50-15/16" x 26-15/16" |
| 5      | 53-1/2" x 41-1/2"  | 50-15/16" x 38-15/16" |
| 6      | 53-1/2" x 59-1/2"  | 50-15/16" x 56-15/16" |
| 7      | 59-1/2" x 41-1/2"  | 56-15/16" x 38-15/16" |
| 8      | 59-1/12" x 59-1/2" | 56-15/16" x 56-15/16" |

#### **Product Identification (Certification Label on Window):**

| System |                                  |                                 |
|--------|----------------------------------|---------------------------------|
| 1-8    | Certification Agency             | WDMA                            |
|        | Manufacturer's Name or Code Name | Pella Corporation               |
|        | Product Name                     | Impervia-Awning                 |
|        | Test Standards                   | AAMA/WDMA/CSA 101/I.S.2/A440-11 |

#### Impact Resistance:

| System | Impact Resistant | Requirement  |
|--------|------------------|--|
| 1-8    | No               | Provide an impact protective system when installing the product in areas that require windborne debris protection. |

## Installation:

| System |                           |   |
|--------|---------------------------|---|
|        | Type of Installation      |   |
|        | Wall Framing              | Install in accordance with Pella drawing No. 1986T, |
| 1-8    | Fasteners                 | dated November 11, 2020. Signed and sealed by       |
|        | Fastener Location/Spacing | Warren W. Schaefer, P.E. on November 18, 2020.      |
|        | Fastener Penetration      |   |

**Note:** Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.