

PO Box 12030 | Austin, TX 78711 | 800-578-4677 | tdi.texas.gov

Product Evaluation

WIN2655 | 0522

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: WIN-2655 **Effective Date:** May 1, 2022

Re-evaluation Date: March 2026

Product Name: Series 0151 Individual and Series 0153 Mulled Vinyl Awning Windows, Fin

Installation, Non-Impact Resistant

Manufacturer: Associated Materials, Inc.

3773 State Rd.

Cuyahoga Falls, OH 44223

(330) 922-5350

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Series 0151 Vinyl Awning Window; X	LC-PG60 (36 x 24)-AP	+60 / -90 psf
2	Series 0151 Vinyl Awning Window; X	LC-PG60 (48 x 24)-AP	+60 / -75 psf
3	Series 0151 Vinyl Awning Window; X	LC-PG55 (48 x 32)-AP	+55 / -55 psf
4	Series 0151 Vinyl Awning Window; X	LC-PG35 (48 x 48)-AP	+35 / -35 psf

General Description:

System	Description	Label Rating	Design Pressure Rating
5	Series 0153 Vinyl Fixed Window over Awning Window; X	LC-PG35 (24 x 60)-AP	+35 / -85 psf
6	Series 0153 Vinyl Fixed Window over Awning Window; X	LC-PG35 (36 x 72)-AP	+35 / -55 psf
7	Series 0153 Vinyl Fixed Window over Awning Window; X	LC-PG35 (48 x 72)-AP	+35 / -40 psf
8	Series 0153 Vinyl Fixed Window over Awning Window; X	LC-PG30 (48 x 96)-AP	+30 / -30 psf

Product Dimensions:

System	Overall Size	Operable Sash Size	Fixed Sash Daylight Opening Size
1	36" x 24"	34-1/2" x 22-1/2"	N/A
2	48" x 24"	46-1/2" x 22-1/2"	N/A
3	48" x 32"	46-1/2" x 30-1/2"	N/A
4	48" x 48"	46-1/2" x 46-1/2"	N/A
5	24" x 60"	22-1/2" x 18-3/4"	18-1/2" x 34-3/4"
6	36" x 72"	34-1/2" x 22-3/4"	30-1/2" x 42-3/4"
7	48" x 72"	46-1/2" x 22-3/4"	42-1/2" x 42-3/4"
8	48" x 96"	46-1/2" x 30-3/4"	42-1/2" x 58-3/4"

Product Identification (Certification Label on Window):

System			
1-4	Certification Agency	AAMA	
	Manufacturer's Name or Code Name	AMI-05	
	Product Name	0151 Awning	
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-08	
5-8	Certification Agency	AAMA	
	Manufacturer's Name or Code Name	AMI-05	
	Product Name	0153/S153 FXD OVER AWN	
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-08	

Impact Resistance:

System	Impact Resistant	Requirement
1-8	No	Provide an impact protective system when installing the
	INO	product in areas that require windborne debris protection.

Installation:

System			
1-4	Type of Installation	Install in accordance with Associated Materials drawing No. TX-5125, dated September 7, 202 Signed and sealed by Lyndon F. Schmidt, P.E. o	
	Wall Framing		
	Fasteners		
	Fastener Location/Spacing	September 7, 2021.	
	Fastener Penetration	September 1, 2021.	
5-8	Type of Installation	In stall in a consultance with A consists of Materials	
	Wall Framing	Install in accordance with Associated Materials	
	Fasteners	drawing No. TX-5126, dated September 7, 202 Signed and sealed by Lyndon F. Schmidt, P.E. of September 7, 2021.	
	Fastener Location/Spacing		
	Fastener Penetration		

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.