TDI Texas Department of Insurance

PO Box 12030 | Austin, TX 78711 | 800-578-4677 | tdi.texas.gov

Product Evaluation

WIN2345 | 0821

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: WIN-2345

Effective Date:August 1, 2021Re-evaluation Date:August 2025

Product Name: Premium Vinyl (V4500) Vinyl Double Hung Windows, Fin and Frame Installation, Impact Resistant

Manufacturer: JELD-WEN Windows and Doors 3737 Lakeport Blvd. Klamath Falls, OR 97601 (541) 850-2650

General Description:

System	Description	Label Rating	Design Pressure Rating	
1	Premium Vinyl (V4500) Vinyl	LC-PG50 (48 x 77)-H	EQ / EE pef	
	Double Hung Windows; X/X	Missile Level C	+50 / -55 psf	
2	Premium Vinyl (V4500) Vinyl	LC-PG50 (48 x 77)-H	+50 / -55 psf	
	Double Hung Windows; X/X	Missile Level D		
3	Premium Vinyl (V4500) Vinyl Triple	LC-PG50 (108 x 72)-H	+50 / -55 psf	
	Double Hung Windows; X/X,X/X,X/X Missile Level		+507-55 psi	
4	Premium Vinyl (V4500) Vinyl Triple	LC-PG50 (108 x 72)-H	EQ / EE pef	
	Double Hung Windows; X/X,X/X,X/X	Missile Level D	+50 / -55 psf	

Product Dimensions:

System	Overall Size	Operable Sash Size	Fixed Sash Daylight Opening Size
1-2	48" x 76-7/8"	44-1/2" x 37-1/4"	45-3/8" x 38-1/8"
3-4	108" x 72"	32-1/8" x 34-1/2"	31" x 33-3/8"

Product Identification (Certification Label on Window):

System		
1-2	Certification Agency	AAMA
	Manufacturer's Name or Code Name	JW-6, JW-18
	Product Name	PREM VYL (V-4500) TILT DH
		AAMA/WDMA/CSA 101/I.S.2/A440-11
	Test Standards	AAMA 506, ASTM E1886/E1996
		Missile Level C (System 1); D (System 2)
3-4	Certification Agency	AAMA
	Manufacturer's Name or Code Name	JW-6, JW-18
	Product Name	PREM VYL (V-4500) TILT TRIPLE DH
		AAMA/WDMA/CSA 101/I.S.2/A440-11
	Test Standards	AAMA 506, ASTM E1886/E1996
		Missile Level C (System 3); D (System 4)

Impact Resistance:

System	Impact Resistant	Requirement	
1, 3	Yes	These products satisfy TDI's criteria for protection from windborne debris. Install in areas where the basic ultimate windspeed is less than 150 mph and greater than one mile from the coastline. Install the assemblies at a height on the structure that does not exceed the design pressure rating for the assemblies.	
2, 4	Yes	These products satisfy TDI's criteria for protection from windborne debris. Install the assemblies at a height on the structure that does not exceed the design pressure rating for the assemblies.	

Installation:

System			
1	Type of Installation	Install in accordance with JELD-WEN drawing with report No. 110-17-126, titled "Premium Vinyl Tilt Double Hung Window-Impact," dated May 6,	
	Wall Framing		
	Fasteners		
	Fastener Location/Spacing	2021. Signed and sealed by Joseph A. Reed, P.E.	
	Fastener Penetration	on June 8, 2021.	
2	Type of Installation	Install in accordance with JELD-WEN drawing with	
	Wall Framing	report No. 110-17-125, titled "Premium Vinyl Till Double Hung Window-Impact," dated May 19,	
	Fasteners		
	Fastener Location/Spacing	2021. Signed and sealed by Joseph A. Reed, P.	
	Fastener Penetration	on June 8, 2021.	
	Type of Installation	Install in accordance with JELD-WEN drawing with	
	Wall Framing	report No. 110-17-129, titled "Premium Vinyl Tilt	
3	Fasteners	Double Hung Window XXX-Impact," dated May 6,	
	Fastener Location/Spacing	2021. Signed and sealed by Joseph A. Reed, P.E.	
	Fastener Penetration	on June 8, 2021.	
	Type of Installation	Install in accordance with JELD-WEN drawing with	
4	Wall Framing	report No. H8907.06-301-47-R0, titled "Premiu	
	Fasteners	Vinyl Tilt Double Hung Window XXX-Impact,"	
	Fastener Location/Spacing	dated May 7, 2021. Signed and sealed by Joseph	
	Fastener Penetration	A. Reed, P.E. on June 8, 2021.	

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.