

PO Box 149104 | Austin, TX 78714 | 1-800-578-4677 | tdi.texas.gov

# **Product Evaluation**

WIN689 | 0523

**Engineering Services Program** 

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

**Evaluation ID:** WIN-689 **Effective Date:** May 1, 2023

**Re-evaluation Date:** May 2027

Product Name: Pella Series 150 / Encompass / Avanti Vinyl Single Hung Windows, Single, Twin,

and Triple, Nail Fin & Block Frame Installation, Non-Impact Resistant

Manufacturer: Pella Corporation

102 Main St. Pella, IA 50219 (641) 621-1000

**General Description:** 

| System | Description  | Label<br>Rating         | Design Pressure<br>Rating |
|--------|--|-------------------------|---------------------------|
| 1      | Series 150 / Encompass / Avanti Single<br>Hung Windows                           | LC-PG35 (40 x 63)-H     | +35 / -35 psf             |
| 2      | Series 150 / Encompass / Avanti High<br>Performance Single Hung Windows          | LC-PG50 (42 x 72)-H     | +50 / -50 psf             |
| 3      | Series 150 / Encompass / Avanti Single<br>Hung Windows                           | LC-PG35 (48 x 84)-H     | +35 / -35 psf             |
| 4      | Series 150 / Encompass / Avanti High<br>Performance Single Hung Windows          | LC-PG50 (52 x 62)-H     | +50 / -50 psf             |
| 5      | Series 150 / Encompass / Avanti High<br>Performance Single Hung Windows;<br>Twin | LC-PG50 (72.5 x 65.5)-H | +50 / -50 psf             |

**General Description (continued):** 

| System | Description  | Label<br>Rating           | Design Pressure<br>Rating |
|--------|--|---------------------------|---------------------------|
| 6      | Series 150 / Encompass / Avanti<br>Single Hung Windows; Twin   | LC-PG35 (96.5 x 53.5)-H   | +35 / -35 psf             |
| 7      | Series 150 / Encompass / Avanti<br>Single Hung Windows; Twin   | LC-PG35 (96.5 x 59.5)-H   | +35 / -35 psf             |
| 8      | Series 150 / Encompass / Avanti<br>Single Hung Windows; Twin   | LC-PG35 (96.5 x 72)-H     | +35 / -35 psf             |
| 9      | Series 150 / Encompass / Avanti<br>Single Hung Windows; Twin   | LC-PG35 (104.5 x 62)-H    | +35 / -40 psf             |
| 10     | Series 150 / Encompass / Avanti<br>Single Hung Windows; Twin   | LC-PG35 (104.5 x 62)-H    | +35 / -50 psf             |
| 11     | Series 150 / Encompass / Avanti<br>Single Hung Windows; Triple | LC-PG35 (107.75 x 53.5)-H | +35 / -35 psf             |
| 12     | Series 150 / Encompass / Avanti<br>Single Hung Windows; Triple | LC-PG35 (109 x 59.5)-H    | +35 / -35 psf             |
| 13     | Series 150 / Encompass / Avanti<br>Single Hung Windows; Triple | LC-PG40 (109 x 72)-H      | +40 / -40 psf             |

### **Product Dimensions:**

| System | Overall Size     | Operable Sash Size     | Fixed Sash Daylight Opening Size |
|--------|------------------|------------------------|----------------------------------|
| 1      | 40" x 63"        | 38" x 30.8125"         | 36.875" x 28.1875"               |
| 2      | 42" x 72"        | 40" x 35.0625"         | 38.875" x 32.9375"               |
| 3      | 48" x 84"        | 46" x 35.0625"         | 44.875" x 44.9375"               |
| 4      | 52" x 62"        | 50" x 30.313"          | 49" x 27.813"                    |
| 5      | 72.50" x 65.50"  | 33.75" x 32.0625" (2)  | 32.625" x 29.4375" (2)           |
| 6      | 96.50" x 53.50"  | 46" x 26.0625" (2)     | 44.875" x 23.4375" (2)           |
| 7      | 96.50" x 59.50"  | 46" x 29.0625" (2)     | 44.875" x 26.4375" (2)           |
| 8      | 96.50" x 72"     | 46" x 35.0625" (2)     | 44.875" x 32.9375" (2)           |
| 9      | 104.50" x 62"    | 50" x 30.313" (2)      | 49" x 27.813" (2)                |
| 10     | 104.50" x 62"    | 50" x 30.313" (2)      | 49" x 27.813" (2)                |
| 11     | 107.75" x 53.50" | 33.625" x 26.0625" (3) | 32.50" x 23.4375" (3)            |
| 12     | 109" x 59.50"    | 34" x 29.0625" (3)     | 32.875" x 26.4375" (3)           |
| 13     | 109" x 72"       | 34" x 35.0625" (3)     | 32.875" x 32.9375" (3)           |

# **Product Identification (Certification Label on Window):**

| System |                      |  |
|--------|----------------------|--|
|        | Certification Agency | WDMA   |
|        | Manufacturer's Name  | Pella Corporation  |
| 1, 3   | Product Name         | Pella 150 Series / Encompass / Avanti - Single<br>Hung           |
|        | Test Standards       | AAMA/WDMA/CSA 101/I.S.2/A440-08, 11                              |
|        | Certification Agency | WDMA   |
|        | Manufacturer's Name  | Pella Corporation  |
| 2, 4   | Product Name         | Pella 150 Series / Encompass / Avanti - HP Single<br>Hung        |
|        | Test Standards       | AAMA/WDMA/CSA 101/I.S.2/A440-08, 11, 17                          |
|        | Certification Agency | WDMA   |
|        | Manufacturer's Name  | Pella Corporation  |
| 5      | Product Name         | Pella 150 Series / Encompass / Avanti - HP<br>2-Wide Single Hung |
|        | Test Standards       | AAMA/WDMA/CSA 101/I.S.2/A440-08, 11                              |
|        | Certification Agency | WDMA   |
|        | Manufacturer's Name  | Pella Corporation  |
| 6-10   | Product Name         | Pella 150 Series / Encompass / Avanti - 2-Wide<br>Single Hung    |
|        | Test Standards       | AAMA/WDMA/CSA 101/I.S.2/A440-08, 11, 17                          |
|        | Certification Agency | WDMA   |
|        | Manufacturer's Name  | Pella Corporation  |
| 11-13  | Product Name         | Pella 150 Series / Encompass / Avanti - 3-Wide                   |
|        |                      | Single Hung  |
|        | Test Standards       | AAMA/WDMA/CSA 101/I.S.2/A440-08, 11                              |

#### **Impact Resistance:**

|   | System | Impact Resistant | Requirement  |
|---|--------|------------------|--|
| ĺ | 1-13   | INO              | Provide an impact protective system when installing the    |
|   | 1-15   |                  | product in areas that require windborne debris protection. |

#### Installation:

| System |                           |  |
|--------|---------------------------|--|
| 1-13   | Type of Installation      | la stall in a secondaria su vitta Della Como anatica                                   |
|        | Wall Framing              | Install in accordance with Pella Corporation   |
|        | Fasteners                 | drawing No. 1572T, Revision B1 dated December 15, 2022. Signed and sealed by Warren W. |
|        | Fastener Location/Spacing | Schaeffer, P.E. on December 19, 2022.  |
|        | Fastener Penetration      | Schaener, P.E. on December 19, 2022.   |

**Note:** Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC and the IBC.